

Summary of quantities by kits				Light repair kit (LRK)	Medium repair kit (MRK)	Arrival Kit (NAK-a)/21 sqm
				per kit	per kit	per kit
REF#	ITEM	Specification and description	Unit	#	#	#
<b>Plastic Sheeting/film LOT</b>						
1	Plastic sheeting heavy duty 190g/m2	UNHCR standards	Pce	3	3	5
2	Clear Plastic film	Nylon transparent, 100 micron thicknes, 4m x 5m	Pce	0	1	1
<b>TIMBER LOT</b>						
1	Timber 80mmx80mmx3 (nominal dimension)	Anti-Stain or Kiln-dried (KD), unfinished surface, ASTM grade 3 or european equivalent, maximum 18% of humidity, +3mm to -1mm section dimension tolerance @ 18% humidity content. Timber to be certified from sustainable harvest according PEFC or FSC or similar international standards	Pce	0	0	12
2	Timber 100mmx50mmx4m (nominal dimension)	Anti-Stain or Kiln-dried (KD), unfinished surface, ASTM grade 3 or european equivalent, maximum 18% of humidity, +3mm to -1mm section dimension tolerance @ 18% humidity content. Timber to be certified from sustainable harvest according PEFC or FSC or similar international standards	Pce	0	4	12
3	Timber 100mmx25mmx4m (nominal dimension)	Anti-Stain or Kiln-dried (KD), unfinished surface, ASTM grade 3 or european equivalent, maximum 18% of humidity, +3mm to -1mm section dimension tolerance @ 18% humidity content. Timber to be certified from sustainable harvest according PEFC or FSC or similar international standards	Pce	0	6	19
<b>TIMBER LOT</b>						
1	Plwywood sheet 8 mm	<b>Canadian Douglas Fir, Finnish Spruce or similar.</b> 3 plies or minimum. Plies laid such that the grain is running in orthogonal directions. 244mmx122mm dimensions	Pce	0	0	1
2	Plwywood sheet 4 mm	<b>Canadian Douglas Fir, Finnish Spruce or similar.</b> 3 plies or minimum. Plies laid such that the grain is running in orthogonal directions. 244mmx122mm dimensions	Pce	0	4	10
<b>Ironmongery LOT</b>						
1	Timber screws	Galvanised mild steel. 4mm shank diameter x 25 mm long. with flat bulge-head, compatible with 6mm wide blade screw driver described below, 400g boxes	Box of 400g	0	1	1
2	Roofing Nails	Galvanised mild steel. 4mm shank diameter x 60 mm long. Domed head. Rubber washers included.	kg	0	1	1
3	Timber nails - 30mm	Galvanised mild steel. 2mm shank diameter x 30mm length. With bulge-head	kg	0	0.5	0.5
4	Timber nails - 50mm	Galvanised mild steel. 4mm shank diameter x 50mm length. With bulge-head	kg	0	0.5	1.5
5	Timber nails - 75mm	Galvanised mild steel. 4mm shank diameter x 75mm length. With bulge-head	kg	0	0.5	1.5
6	Steel angle sections	Galvanised mild steel. Folded into 90 degree angle. Minimum size = 10x10x2.5cm (i.e. each out-stand leg = 10cm long). Minimum plate thickness = 3mm. Pre-drilled with minimum 3 holes per out-stand leg.	Piece	0	10	15
7	Rubber Ties	Black, square section 15mm. Roll of 50 meters	Piece	0	1	1
8	Stapler (with adequate staples)	Stapples Gun Tacker - Medium Duty - Manual To be provided with staples (1500 pces) : - Galvanized Steel wire - U Shapes - Stiff flat wire (crown width : 12 - 13mm; Width : ~1mm to 1.2mm; Leg length : 12-13 mm; Thickness :0.7-0.8 mm	Piece	0	1	1
9	Hinges	Galvanised mild steel. T-shaped barrel hinge. Minimum 15cm long x 3cm wide outstand arm. Minimum 7cm long x 3cm wide base-plate. Pre-drilled with minimum 4 no. of holes on each side of the hinge	Piece	0	0	3
10	Hasp	Galvanised mild steel. Minimum 10cm length x 3cm wide. Minimum 4 no. pre-drilled holes per component for fixing. To be compatible with padlock described below.	Piece	0	0	1
11	Padlock	Galvanised mild steel. Body size minimum 4x4x2cm. Shackle minimum 6mm diameter. To be supplied with minimum 2 no. keys	Piece	0	0	1
12	Flue Pipe	Galvanised mild steel or stainless steel tube. Minimum 15cm diameter x 50cm length. Preferably with minimum 50mm width out-stand flange (collar) welded to exterior of tube.	Piece	0	1	1
<b>Tool LOT</b>						
1	Carpentary Hammer	Minimum overall length = 35cm long. Wooden or rubber-coated handle. Solid metal head with curved claw. Weight ~ 700 gr	Piece	0	1	1
2	Wood Saw	Minimum overall length = 50cm long. Wooden or rubber-coated handle. Tapered	Piece	0	1	1
3	Cutter	("Stanley knife") - plastic or rubber handle - 2 pcs spare blades	Piece	0	0	1
4	Screw-driver	6mm wide blade-head, Shaft length:12.5cm, Minimum overall length:22cm.Wooden or rubber-coated handle. Fully insulated. Small mains tested:200-250 volts AC. Must fit wood-screws listed above	Piece	0	1	1
5	Tape Measure	10m length. Hand-coil (not sprung). Circular/disc-shaped. Preferred metal case	Piece	0	0	1
<b>Packaging LOT</b>						
1	Cartoon storage box (A)	- Strong cartoon box, 5 layers of cartoon where white platic film, Ironmongery and tools will be packed - Branding : sticker of 18cm x 12cm - printed with 2 colors - Dim : small size to be specified later	Piece	0	0	0
2	Cartoon storage box (B)	- Strong cartoon box, 5 layers of cartoon where white platic film, Ironmongery and tools will be packed - Branding : sticker of 18cm x 12cm - printed with 2 colors - Dim : small size to be specified later	Piece	0	1	0
3	Cartoon storage box ©	- Strong cartoon box, 5 layers of cartoon where white platic film, Ironmongery and tools will be packed - Branding : sticker of 18cm x 12cm - printed with 2 colors - Dim : 56 x 39 x 15 height	Piece	0	0	1
4	Assembly note/tips	- Type leaflet A4 - #pages : 2- 6 - paper quality: 350grs, laminated - printed full color - To be inserted in the the box mentioned above	Piece	0	1	1